

FOR CALIFORNIA RESIDENTS ONLY:
WARNING! This product can expose you to chemicals including Carbon Monoxide, that is an externally vented by-product of fuel consumption, which is [are] known to the State of California to cause birth defects or other reproductive harm. For more information, visit **www.P65Warnings.ca.gov.**

Unit Illustrated:
ZCV3622N Zero Clearance Direct Vent Gas Fireplace (Natural Gas), LOGC51 Log Set (Oak), ZCV3622PRL Porcelain Reflective Liner, ZCV3631BL Surround (Hearth Mount – Black).

Intertek
4000720

Marquis Fireplaces maintains a program of continuous testing, refinement and improvements of all its products. Some aspect of units shown here may be changed at any time without notice or obligation.

Certification: Certified to ANSI Z21.88, CSA 2.33 Vented Gas Fireplace Heaters.

Note: Components may have to be ordered separately to create a complete unit. Discuss with your local Marquis Dealer for clarification.

Canada
ENERGUIDE

Look for the EnerGuide Gas Fireplace Energy Efficiency Rating in this brochure

Based on CSA P.4.1-15

Crafted entirely in Canada, each Marquis fireplace is built to the highest standards and made to last.

LIMITED LIFETIME WARRANTY

2340 Logan Avenue
Winnipeg, Manitoba, CAN
R2R 2V3
Phone: 204.632.1962
Fax: 204.632.1960
marquisfireplaces.net

Printed in Canada
8092 – 06/2026



marquis
FIREPLACE | COLLECTION

Unit Illustrated:
ZCV3622N Zero Clearance Direct Vent Fireplace (Natural Gas), LOGC51 Log Set (Oak), ZCV3622ML Metal Brick Liner.

(Finishing materials that cover the Fireplace must be non-combustible materials.)

Solara II

Zero Clearance Direct Vent Gas Fireplace

Add some **sizzle.**

Incredibly versatile, the Solara is perfectly at home with a classic mantle or contemporary wall surround. Plus you can also choose a log set or a contemporary rock set.

Visit **marquisfireplaces.net** to see the latest evolution in fireplaces.

Standard Features

- Millivolt or IPI valve system allows operation during a power failure with Hi/Low heat and flame adjustment
- Proprietary burner, with realistic burn
- Mobile Home, Bedroom and Bed Sitting Room approved
- Safety Screen Barrier

Optional Features

Surrounds:
Hearth Mount: Black (Coverage: 34 ⅛"H x 39"W)
Flatt: Black (Coverage: 37 ¼"H x 40 ⅞"W)

Accessories:
Log set or rock set required

Liners:
Porcelain Reflective Liner or Metal Brick Liners

Fan Kit:
Heat activated with variable speed control

Thermostat:
Wall Mount or Programmable

Remote:
Thermostat On/Off, Thermostat On/Off modulating, Thermostat On/Off modulating and fan control

Wall Mount Battery Holder (WMBH):
The battery holder provides power to the IPI system in case of power failures. Locating the battery holder outside of the fireplace (wall mount) provides a convenient and accessible location for battery installation and removal.

FIND ALL DETAILED SOLARA MANUALS



Unit Illustrated:
ZCV3622N Zero Clearance Direct Vent Natural Gas Fireplace, MQROCK2 Rock Set (Natural) ZCV36SWFBL Surround (Flatt – Black), ZCV3622PRL Liner (Porcelain Reflective).

Specifications

MODELS >	ZCV3622N	ZCV3622NE	ZCV3622LP	ZCV3622LPE
Fuel	Natural Gas	Natural Gas	Propane	Propane
Input Max.	18,000 BTU	18,000 BTU	18,000 BTU	18,000 BTU
Input Min.	13,000 BTU	13,000 BTU	15,000 BTU	15,000 BTU
FE (P.4.1-15)	60.54%	63.46%	62.09%	65.09%

Product Dimensions

ZCV3622 – TOP FLUE MODEL


FRAMING DIMENSIONS

A 53 ½"
B 36"
C 36 ⅜"
D 8 ⅝"
E 37 ⅞"
F 26 ¾"

VIEWING AREA

Width 29 ¾"
Height 18 ⅝"

	Actual	Framing
Height	33 ½"	37 ¼"
Front Width	36"	36 ⅜"
Depth	17 ⅞16"	17 ½"





Unit Illustrated:
ZCV3622N Zero Clearance Direct Vent Fireplace (Natural Gas), ZCV36SWFBL Surround (Flatt – Black), LOGC51 Log Set (Oak), ZCV3622PRL Porcelain Reflective Liner.

Accessories

MEDIA OPTIONS



LOGC51 Split Oak Log Set



MQROCK2 Natural Rock Set

LINERS




PL Porcelain Reflective




Metal Brick

SURROUNDS



ZCV36S1BL Hearth Surround



ZCV36SWFBL Flatt Surround

REMOTE



PF1

THERMOSTAT



Z80PT Wall Mount