LINEAR GAS FIREPLACES



enviro.com





Ledgestone Liner – Bezel Base



Fluted Liner – Bezel Base



Black Enameld Liner – Bezel Base



Ledgestone Liner – Ultra High Definition Log Set



Fluted Liner – Ultra High Definition Log Set



Black Enameld Liner – Ultra High Definition Log Set







Ledgestone Liner – Bezel Base



Fluted Liner – Bezel Base



Black Enameld Liner – Bezel Base



Ledgestone Liner – Ultra High Definition Log Set



Fluted Liner – Ultra High Definition Log Set



Black Enameld Liner – Ultra High Definition Log Set





Cool Surface System HDK

In the past, wall mounted televisions or treasured decor pieces would degrade over time from the excess rising heat produced by your gas fireplace. Our new Cool Surface System for the C Series allows you to make use of the valuable real estate directly above your linear gas fireplace. It can channel heat inside the wall and vent it out above the fireplace.

Opening bezel can be painted to blend with wall color

Dual vents reduce surface temperature and evenly channel rising heat



These side ducts can be installed in a horizontal or vertical format and high temp paint (250°F) can be used on the opening bezels to blend with wall color





Ledgestone Liner – Full Glass Tray



Fluted Liner – Full Glass Tray



Black Enameld Liner – Full Glass Tray



Ledgestone Liner – Bezel Base



Fluted Liner –Bezel Base



Black Enameld Liner – Bezel Base







Ledgestone – Rock & Log Set



Fluted Liner – Rock & Log Set



Black Enameld Liner – Rock & Log Set



Ledgestone Liner – Full Glass Tray



Fluted Liner – Full Glass Tray



Black Enameld Liner – Full Glass Tray



Specifications	C34			C44			C60		
BTU Maximum Input - NG / LP	30,000 BTU's			38,000 BTU's			51,000 BTU's		
BTU Minimum Output* - NG / LP	9,750 BTU's			12,255 вти′ѕ			16,702 BTU's		
Turn Down - Valve 820 / Valve 885	Up to 50%			Up to 50%			Up to 50%		
FE Efficiency **	64.6%			64.5%			65.7%		
Valve Configuration	Standing Pilot & IPI			Standing Pilot & IPI			Standing Pilot & IPI		
Venting	5" / 8"			5" / 8"			5" / 8"		
Flex Venting	Up to 10'			Up to 10'			Up to 10'		
Glass Size	HEIGHT 14"		WIDTH 34½"	HEIGHT 14"		WIDTH 44½"	HEIGHT 14"		WIDTH 601/2"
Visible Dimensions	165/8"		361/8"	16¼"		461/8"	165/8″		621/8"
Minimum Framing Dimensions †	HEIGHT 38"	WIDTH 45"	DEPTH 20 "	HEIGHT 38"	WIDTH 55"	DEPTH 20 "	HEIGHT 38"	WIDTH 71 "	DEPTH 20 "

^{**}Calculated by (Max BTU Input) × 50% (Turn Down Valve) × (FE Efficiency, emissions and area heated varies by venting & location. Tested to P4.1-15 | † Please refer to owners manual for detailed installation instructions.



Optional Surround

Create stronger focus on the flames by adding a brushed nickel, brushed antique copper, brushed black nickel, or powder coated borderview surround.



Cool Surface System HDK

This heat distribution / TV kit channels hot air away from wall mounted TV's placed directly above the unit. It is available in front facing or side vent configurations.



Hidden Pilot System

The C Series uses a hidden pilot system diagonally recessed on a far edge so as not to obstruct the overall look of the burn.



Optional Dual Blower Kit

This optional 220 CFM fan assembly operates with a left and right fan to help evenly push warm air further into the room.

Fluted Liner



Compatible with the C34, C44, and C60

Compatible with the C34, C44, and C60

Ultra High Definition Log Set Traditional Log Set



Compatible with the C34 and C44

Rock & Log Set



Compatible with the C44 and C60

Ledgestone Liner



Compatible with the C34, C44, and C60

Halogen Light Kit



Compatible with the C34, C44, and C60

Black Enameled Liner



Compatible with the C34, C44, and C60

Bezel Base



Includes Black Glass Media or Vermiculite Compatible with the C34, C44, and C60

Full Glass Tray



19

Compatible with the C34, C44, and C60

Iron Spheres Kit



Compatible with the C34, C44, and C60









