Q 1 PORTRAIT GAS FIREPLACE / INSERT





Design Features

- Clean Face Look No Louvers
- SIT Valve 820 (Standing Pilot)
- SIT Valve 885 (IPI System with Remote)
- Glass Size: 17¹/₂" x 19³/₄", 345¹/₂ in²
- Classic Log Set
- 150 CFM Room Fan (with variable control)
- Limited Lifetime Warranty
- ClearView Safety Screen
- Quick Access Valve Controls

Available Options

- Remote or Thermostat Control
- Glass, Coal, or Log Set
- Liners Options:
 - Brick Liner with Logs or Coal
 - Black Enameled Liner with Glass or Logs
 - Ledgestone Liner
- Surround Options:
 - Victorian Face
 - Minimal Surround
 - Modern Surround
 - Contemporary Surround w/Trimmable Panel
 - Trimmable Panel

Insert Specifications

BTU Maximum Input - NG	20,000 BTU
BTU Minimum Output*	7,450 BTU
Heating Area	1,000 ft ²
P4 Efficiency	74.5%
Glass Size	345½ in ²
Minimum Install Dims. ⁺	HEIGHT WIDTH DEPTH 271⁄2" 201⁄4" 141⁄4"

* Turn down is based on a 50% valve and P4 efficiencies output.

† Based on installation with the Contemporary Surround. Depth can vary by panel.