

MODEL: Distinction DL6315ST

STYLE: See Through

DESCRIPTION	FEATURES
A modest version of the Distinction D6315ST, the DL6315ST still features characteristics that make it stand out from the rest of the pack. The concealed burner allows the burner to be covered with glass or stone media. The unit is fully upgradable, with all the features available in the D6315ST available in the DL6315ST.	<ul style="list-style-type: none"> • Clean face design • 40,000 BTU/HR NG or LP • Montigo 4TH generation linear concealed burner • Borosilicate glass door • IPI Electronic Ignition • Power vent compatible • Star ice fireglass

GLASS		VENTING	
Viewing Area	63" wide x 14 3/8" high	Size	5"/8" Direct Vent
Type	Borosilicate glass	Location	Top middle

GAS	
Max BTU Natural Gas	40,000 BTU/hr
Max BTU Propane	40,000 BTU/hr
Nominal Inlet pressure	3.8" w.c. / 11" w.c.
Control System	Proflame 2 IPI BASIC
Burner Style	Concealed linear ribbon burner

COMPONENTS	
Power Venting	Optional, Montigo roof mount, wall mount or inline power vent
Electrical	120 VAC, 60 Hz, 1Ph, 5A
Clearances	Sides: 3 1/3", Back: 2", Top: 38 1/4", Floor: 0"
Control	On/Off wall switch
Testing standards	ANSI Z21.50/ CSA 2.22-2014 and ANSI Z21.97/ CSA 2.41-2014
Media options	Firestones, fireglass, speckled stones, driftwood logset