



MODELS: Distinction D6315 STYLE: Single Sided

-	ES		p)	I p	20	Ta.	1.1
	70.1	.9	AT.	l id	111	ſω,	IA.

The D6315 is a full load single sided direct vent fireplace characterized by a generous landscape viewing area and linear burner. The concealed burner allows the burner to be covered with glass or stone media. Additional features underneath the burner include multicolor LED lighting and a standard circulating fan kit.

## FEATURES

- Clean face design
- 50,000 BTU/HR NG or LP
- Montigo 4<sup>TH</sup> generation linear concealed burner
- Ceramic glass door
- 50% turn down gas valve with steppermotor
- IPI Electronic Ignition
- Power vent compatible Full Feature Proflame 2 remote control
- Quiet circulating fans with remote speed adjustment
- Ceramic glass reflective liner, multicolor LED lighting, star ice fireglass
- Invisimesh screen

GLASS	
Viewing Area	63" wide x 14 3/8" high
Type	Ceramic glass

VENTING	
Size	5"/8" Direct Vent
Location	Top middle

GAS	
Max BTU Natural Gas	50,000 BTU/hr
Max BTU Propane	50,000 BTU/hr
Nominal Inlet pressure	3.8" w.c. / 11" w.c.
Control System	Proflame 2 IPI
Burner Style	Concealed linear ribbon burner

COMPONENTS	
Power Venting	Optional, Montigo roof mount, wall mount or inline power vent
Electrical	120 VAC, 60 Hz, 1Ph, 5A
Clearances	Sides: 3 1/3", Back: 2", Top: 38 1/4", Floor: 0"
Control	Proflame 2 remote control, LED lighting remote control
Testing standards	ANSI Z21.50/ CSA 2.22-2014 and ANSI Z21.97/ CSA 2.41-2014
Media options	Firestones, fireglass, speckled stones, driftwood logset