



24-DVRS25N

Eloquence

Direct Vent Gas Fireplace



Eloquence, Style and Warmth

Specifically designed to fit in tight spaces where other units can't, Brigantia's all new 24-DVRS25N direct vent gas fireplace adds a touch of style and warmth to any room.



24-DVRS25N

Eloquence

Direct Vent Gas Fireplace

SPECIFICATIONS

Input Rating

Natural Gas	14,000 - 25,000 BTU/HR / 4.10 - 7.33 KW
Propane	14,000 - 25,000 BTU/HR / 4.10 - 7.33 KW

Efficiencies

Maximum Efficiency	82%
P4	71%

Standard Features

Remote Control	Flame, programmable thermostat and timer
Interior Lining	Black fiber
Ceramic Glass Door	Included
Viewing Area	15-1/2" W x 18-3/4" H
Vent Size	4 x 6-5/8" rigid, rear, 4 x 7" flex
Burner Type	Wall to Wall Steel Pan
Firebox and Host Shell Construction	Welded/rivet and gasket, silicone free Host shell has removable firebox which allows the shell to be installed without the firebox
Warranty	Limited lifetime

Options

Interior Lining	Reflective Glass Panel
Propane Conversion kit	Optional
Door	Black or Brushed Nickel
Surround	Black or Brushed Nickel

Clearance to Combustibles

Framing Dimensions	26-1/2" W x 39-1/2" H x 5-1/2" D
Room Clearances Measured to Outer Shell	Sidewall 4" (102mm) Floor 4" (102mm) Ceiling 12" (305mm) Mantel = 9" (229mm) (Based on 8" (203mm) deep mantel)

See owner's manual for framing instructions and clearance to combustible guides.

All information on this literature is subject to change at the discretion of the manufacturer.

FRONT PANELS



Brushed Nickel Door with Brushed Nickel Surround



Black Door with Black Surround



Brushed Nickel Door with Black Surround



Black Door with Brushed Nickel Surround

