



35-DVRS31N
Perfection
Direct Vent Gas Fireplace



Perfection, Comfort and Style
Specifically designed to fit in tight spaces where other units can't,
Brigantia's all new 35-DVRS31N direct vent gas fireplace adds
a touch of style and warmth to any room.



35-DVRS31N Perfection Direct Vent Gas Fireplace


SPECIFICATIONS

Input Rating	
Natural Gas	16,000 - 31,000 BTU/HR / 4.69 - 9.1 KW
Propane	16,000 - 31,000 BTU/HR / 4.69 - 9.1 KW
Efficiencies	
Maximum Efficiency	84%
P4	72%
Standard Features	
Remote Control	Flame, programmable thermostat and timer
Interior Lining	Black fiber
Ceramic Glass Door	Included
Viewing Area	31" W x 17" H
Vent Size and Location on Unit	4 x 6-5/8" rigid, 4 x 7" flex, terminates vertical or horizontal
Burner Type	Wall to Wall Steel Pan
Firebox and Host Shell Construction	Welded/rivet and gasket, silicone free Host shell has removable firebox which allows the shell to be installed without the firebox
Warranty	Limited Lifetime
Options	
Interior Lining	Reflective Glass Panel
Propane Conversion Kit	Optional
Door	Black or Brushed Nickel
Surround	Black or Brushed Nickel
Clearance to Combustibles	
Framing Dimensions	42-1/2" (1080mm) W x 42" (1067mm) H x 5-1/2" (140mm) D
Room Clearances Measured to Outer Shell	Sidewall 4" (102mm) Floor 4" (102mm) Ceiling 14" (356mm) Mantel = 9" (229mm) (Based on 8" (203mm) deep mantel)
Host Shell clearance to combustibles 0" to standoff. See owner's manual for framing instructions and clearance to combustible guides.	
All information on this literature is subject to change at the discretion of the manufacturer.	

FRONT PANELS



Brushed Nickel Door with Brushed Nickel Surround



Black Door with Black Surround



Brushed Nickel Door with Black Surround



Black Door with Brushed Nickel Surround

