

Solaira RADIUS Electric Radiant Heater

Hospitality | Clubs and Resorts | Custom Homes | Sporting Venues





Solaira<sup>2</sup>

# **RADIUS**

Electric Radiant Pendant Heater

The Radius electric infrared pendant heater combines exceptional heating performance and elegant design. With a high radiant heat output, broad voltage range and versatile ceiling mount capability, the Solaira Radius is the perfect solution for projects demanding both powerful heating and architectural sophistication

- where high performance meets timeless design.







#### **Finish Colors**







## **Key Features**

POWER (WATTS)	4500W / 15,400 BTU   3000W / 10,200 BTU				
CONSTRUCTION	Aluminum + Stainless Steel				
GRILLE	High-Temperature Ceramic Glass				
COATING	UV Resistant Polyester Powder coating, BLACK, WHITE				
HEAT SOURCE	Solaira° Ultra Low-glare emitter				
POWER SOURCE	208V, 240V				



CERTIFIED TO CSA STD 22.2 NO.46 CONFORMS TO UL



## **Tech Specs**

MODEL	POWER (WATTS)	BTU's	VOLTS	AMPS	WEIGHT
GRAD30208-B GRAD30208-W**	3000W	10,200	208	14.4A	
GRAD30240-B GRAD30240-W**	3000W	10,200	240	12.5A	70LDC / 14 EVC
GRAD45208-B GRAD45208-W**	4500W	15,350	208	21.6A	32LBS / 14.5KG
GRAD45240-B GRAD45240-W**	4500W	15,350	240	18.8A	

<sup>\* -</sup>W INDICATES WHITE, -B INDICATES BLACK
\*\* WHITE HEATERS AVAILABLE BY SPECIAL ORDER ONLY



#### DATA-DRIVEN HEATER LAYOUTS AVAILABLE

Solaira's HEAT SPEC tool delivers elevated heater coverage visualizations. Requesting a HEAT SPEC layout removes the guess work of heater placement and allows you to define and specify heatrise for a target area. Request a HEAT SPEC Layout from your sales rep.

MODEL	MOUNTING HEIGHT	DIAMETER	HEAT DENSITY WATTS/SQ Ft
GRAD30208 GRAD30240	8' (2.4m)	8' (2.4m)	20 W/SF
GRAD45208 GRAD45240	8' (2.4m)	10' (3.1m)	20 W/SF
	10' (3.1m)	12' (4.3m)	15 W/SF



